

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/06/2023 Revision date: 19/08/2024 Supersedes version of: 09/11/2023 Version: 6.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 801801 - TOP AUTOMATIQUE BLANC
Product code : 801801
Type of product : Aerosol, Paints
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

ITW Spraytec
42, rue Gallieni
FR F-92600 Asnières sur Seine
France
T +33(0)1.40.80.32.32, F +33(0)1.40.80.32.30
infods@itwpc.com, www.itwpc.com

Distributor

ROCOL a division of ITW Ltd
ROCOL House
Wakefield Rd, Swillington
UK LS26 8BS Leeds
United Kingdom
T +44 (0)113 232 2600
customer.service@rocol.com, www.rocol.com

1.4. Emergency telephone number

Emergency number : FRANCE :+ 33 (0)1 45 42 59 59

Country/Area	Organisation/Company	Address	Emergency number	Comment
Austria	Vergiftungsinformationszentrale	Stubenring 6 1010 Vienna	+43 1 406 43 43	
Belgium	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Bulgaria	Национален токсикологичен информационен център Многопрофилна болница за активно лечение и спешна медицина "Н.И.Пирогов"	бул. Ген. Едуард И. Тотлебен 21 1606 Sofia	+359 2 9154 233	The phone is active 24/7 and calls to it are free
Croatia	Centar za kontrolu otrovanja Institut za medicinska istraživanja i medicinu rada	Ksaverska Cesta 2 p.p. 291 10000 Zagreb	+385 1 234 8342	Information available 24/7 in Croatian and English
Cyprus	Κέντρου Δηλητηριάσεων	Nicosia	1401	Operating hours 24 hours / 24 hours, 7 days a week

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Czech Republic	Toxikologické informační středisko Klinika pracovního lékařství VFN a 1. LF UK	Na Bojišti 1 120 00 Prague	+420 224 919 293 +420 224 915 402	and only in the event of a malfunction, phone 725 103 658 (otherwise there may not be a toxicologist on this phone!) Questions about ACUTE INTOXICATION of people and animals are dealt with exclusively on TIS direct telephone lines 24 hours a day
Denmark	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23E Opgang 20 C 2400 Copenhagen	+45 82 12 12 12	
Estonia	Mürgistusteabekeskus Terviseamet	Paldiski mnt 81 10614	16662 +372 7943 794	Calling the hotline is anonymous and at the cost of a local call.
Finland	Myrkytystietokeskus	Stenbäckinkatu 9 PO BOX 100 00029 Helsinki	+358 800 147 111 +358 9 471 977	Open 24 hours a day 0800 147 111 (free of charge) 09 471 977 (normal rate call)
Germany	BfR Bundesinstitut für Risikobewertung / German Federal Institute for Risk Assessment	Max-Dohrn-Str. 8-10 10589 Berlin	+49-30-18412-0	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Latvia	Valsts ugunsdzēsības un glābšanas dienests Toksikoloģijas un sepses klīnikas Saindēšanās un zāļu informācijas centrs	Hipokrāta 2 1038 Riga	112 +371 67 04 24 73	works 24 hours a day
Lithuania	Apsinuodijimų informacijos biuras	Šiltnamių g. 29 04130 Vilnius	+370 (5) 236 20 52	
Luxembourg	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, Dutch and English
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)
Norway	Giftinformasjonen	Folkehelseinstituttet Postboks 222 Skøyen 0213 Oslo	+47 22 59 13 00	Operating hours 24 hours / 24 hours, 7 days a week

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Poland	Szpital Praski p.w. Przemienienia Pańskiego Sp. z o.o.	Aleja Solidarności 67 03-401 Warsaw	+48 22 619 66 54 +48 22 619 08 97	
Portugal	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica	Rua Almirante Barroso, 36 1000-013	+351 800 250 250	
Romania	TOXAPEL Spitalul Clinic de Urgenta pentru Copii „Grigore Alexandrescu”	Boulevardul Iancu de Hunedoara 30-32 Bucharest	+40 2121 06282 +40 2121 06183	
Slovakia	Národné toxikologické informačné centrum Univerzitná nemocnica Bratislava, pracovisko Kramáre, Klinika pracovného lekárstva a toxikológie	Limbová 5 833 05 Bratislava	+421 2 54 77 41 66 +421 911 166 066	
Slovenia	Center za klinično toksikologijo in farmakologijo Univerzitetni klinični, Center Ljubljana	Zaloška 7 1000 Ljubljana	112	
Spain	Servicio de Información Toxicológica Instituto Nacional de Toxicología y Ciencias Forenses, Departamento de Madrid	C/José Echegaray nº4 28232 Las Rozas de Madrid	+34 91 562 04 20 +34 91 411 26 76 (teléfono solo para médicos)	(Toxicological emergencies only). Information in Spanish (24/7)
Sweden	Giftinformationscentralen	Solna Strandväg 21 171 54 Solna	112 – begär Giftinformation	
Switzerland	Tox Info Suisse	Freiestrasse 16 8032 Zürich	145 +41 44 251 51 51	(from abroad: +41 44 251 51 51) non urgent inquiry: +41 44 251 66 66
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

801801 - TOP AUTOMATIQUE BLANC


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: Acetone; Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (containing < 0,1 % butadiene (203-450-8)) (Propellant gas (Aerosol)) (Note C)(Note U)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	20 – 40	Flam. Gas 1, H220 Aerosol 1, H222;H229 Press. Gas (Diss.), H280
Propane (Propellant gas (Aerosol)) (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	< 15	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	< 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Hydrocarbons, C6, isoalkanes, <5% n-hexane (Note P)	CAS-No.: 64742-49-0 EC-No.: 931-254-9 EC Index-No.: 649-328-00-1 REACH-no: 01-2119484651-34	< 15	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Carbon dioxide (Propellant gas (Aerosol))	CAS-No.: 124-38-9 EC-No.: 204-696-9	< 10	Press. Gas (Comp.), H280
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	< 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	< 5	Flam. Liq. 3, H226 STOT SE 3, H336
	CAS-No.: none available EC-No.: 920-750-0 REACH-no: 01-2119473851-33	< 5	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a POISON CENTER/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a POISON CENTER/doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking. Causes skin irritation.
Symptoms/effects after eye contact	: Eye irritation. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water haze. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Thermal decomposition generates : fume. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel.
----------------------	---

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Heat sources. Sources of ignition. Direct sunlight.
- Storage temperature : < 50 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
France - Occupational Exposure Limits	
Local name	n-Butane
VME (OEL TWA)	1900 mg/m ³
	800 ppm
Remark	Valeurs recommandées/admises

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA)	1450 mg/m ³
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
	750 ppm
Remark	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon dioxide (124-38-9)	
France - Occupational Exposure Limits	
Local name	Carbone (dioxyde de)
VME (OEL TWA)	9000 mg/m ³
	5000 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrêté du 26 octobre 2007)
United Kingdom - Occupational Exposure Limits	
Local name	Carbon dioxide
WEL TWA (OEL TWA)	9150 mg/m ³
	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m ³
	15000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Acetone (67-64-1)	
France - Occupational Exposure Limits	
Local name	Acétone
VME (OEL TWA)	1210 mg/m ³
	500 ppm
VLE (OEL C/STEL)	2420 mg/m ³
	1000 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acetone (67-64-1)	
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
France - Occupational Exposure Limits	
Local name	propane-2-ol, alcool isopropylique, isopropanol
VLE (OEL C/STEL)	980 mg/m ³ 400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-Propanol, Isopropylalkohol, Isopropanol
AGW (OEL TWA)	500 mg/m ³ 200 ppm
AGW (OEL C)	1000 mg/m ³
AGW (OEL C) [ppm]	400 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m ³ 400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³ 500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
France - Occupational Exposure Limits	
Local name	Acétate de n-butyle
VME (OEL TWA)	710 mg/m ³ 150 ppm
VLE (OEL C/STEL)	940 mg/m ³ 200 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	n-Butylacetat
AGW (OEL TWA)	300 mg/m ³ 62 ppm
AGW (OEL C)	600 mg/m ³
AGW (OEL C) [ppm]	124 ppm

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m ³
	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
xylene (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene, o-,m-,p- or mixed isomers
WEL TWA (OEL TWA)	220 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
	100 ppm
Remark	Sk, BMGV
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-methoxy-1-methylethyl acetate (108-65-6)	
France - Occupational Exposure Limits	
Local name	Acétate de 2-méthoxy-1-méthyléthyle
VME (OEL TWA)	275 mg/m ³
	50 ppm
VLE (OEL C/STEL)	550 mg/m ³
	100 ppm
Remark	Valeurs réglementaires contraignantes. Risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA)	274 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	548 mg/m ³
	100 ppm
Remark	Sk

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

In case of repeated or prolonged contact wear gloves. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent). The choice of appropriate gloves depends not only on the material, but also on other quality criteria that may vary from one manufacturer to another. As the product is a preparation made from several substances, glove material resistance may not be calculated in advance and must be tested before use. The exact penetration time of glove material is to be determined by the manufacturer of protective gloves and respected. Wear protective gloves.

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Odour	: Organic solvent.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: < 0 °C
Flammability	: Extremely flammable aerosol, Non flammable.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 0 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: soluble in most organic solvents. insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,96 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 84,8847 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

None under normal conditions. Not established.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	≈ 76 mg/l/4h
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)

LD50 oral rat	> 36750 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 3350 ml/kg
LC50 Inhalation - Rat	259354 mg/l/4h
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg Source: ECHA
LD50 dermal rabbit	12800 mg/kg Source: ECHA

n-butyl acetate (123-86-4)

LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 Inhalation - Rat	23,4 mg/l/4h
LC50 Inhalation - Rat (Vapours)	1802 mg/l Source: ECHA

2-methoxy-1-methylethyl acetate (108-65-6)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	23,8 mg/l /6H
LC50 Inhalation - Rat [ppm]	4345 ppm /6H

(none available)

LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation : Causes skin irritation.
Additional information : Repeated exposure may cause skin dryness or cracking.

Carbon dioxide (124-38-9)

pH	3,2 Source: HSDB
----	------------------

Acetone (67-64-1)

pH	5 Source: ECHA
----	----------------

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
pH	6,2
Serious eye damage/irritation	: Causes serious eye irritation.
Carbon dioxide (124-38-9)	
pH	3,2 Source: HSDB
Acetone (67-64-1)	
pH	5 Source: ECHA
n-butyl acetate (123-86-4)	
pH	6,2
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
2-methoxy-1-methylethyl acetate (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.
(none available)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LOAEC (inhalation, rat, vapour, 90 days)	16,6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapour, 90 days)	3,3 mg/l air Animal: rat, Animal sex: male

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
xylene (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
(none available)	
NOAEC (inhalation, rat, vapour, 90 days)	24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard

: Not classified

Additional information

: Based on available data, the classification criteria are not met

801801 - TOP AUTOMATIQUE BLANC	
Vaporizer	Aerosol
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Vaporizer	Aerosol
Acetone (67-64-1)	
Viscosity, kinematic	0,417 mm ² /s
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Viscosity, kinematic	0,46 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0,83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
xylene (1330-20-7)	
Viscosity, kinematic	< 0,9 mm ² /s
(none available)	
Viscosity, kinematic	0,715 – 0,786 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: Harmful to aquatic life with long lasting effects.

Ecology - water

: Harmful to aquatic life with long lasting effects.

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Carbon dioxide (124-38-9)	
LC50 - Fish [1]	35 mg/l Source: HSDB
Acetone (67-64-1)	
LC50 - Fish [1]	5540 – 11000 mg/l
EC50 - Crustacea [1]	8800 mg/l
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	430 mg/l
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LC50 - Fish [1]	> 1 mg/l
LC50 - Other aquatic organisms [1]	2,6 mg/l Source: IUCLID
EC50 - Crustacea [1]	3,87 mg/l
ErC50 algae	30 mg/l
LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LC50 - Fish [1]	9640 mg/l Source: ECHA
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	674,7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	647,7 mg/l
LOEC (chronic)	47,6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	200 mg/l
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 500 mg/l
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	> 1000 mg/l
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47,5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(none available)	
LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

801801 - TOP AUTOMATIQUE BLANC	
Persistence and degradability	May cause long-term adverse effects in the environment.
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Persistence and degradability	Rapidly degradable
Propane (74-98-6)	
Persistence and degradability	Rapidly degradable
Carbon dioxide (124-38-9)	
Persistence and degradability	Not established.
Acetone (67-64-1)	
Persistence and degradability	Not established.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Persistence and degradability	May cause long-term adverse effects in the environment.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Persistence and degradability	Not established.
n-butyl acetate (123-86-4)	
Persistence and degradability	Not established.
xylene (1330-20-7)	
Persistence and degradability	Not established.
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Not established.
(none available)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

801801 - TOP AUTOMATIQUE BLANC	
Bioaccumulative potential	Not established.
Carbon dioxide (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0,83
Bioaccumulative potential	Not established.
Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0,24 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-0,24
Bioaccumulative potential	Not established.

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Partition coefficient n-octanol/water (Log Pow)	2,1 – 6 Source: IUCLID
Partition coefficient n-octanol/water (Log Kow)	4
Bioaccumulative potential	Not established.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0,05 Source: ICSC
Bioaccumulative potential	Not established.
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1,78 Source: HSDB
Partition coefficient n-octanol/water (Log Kow)	2,3
Bioaccumulative potential	Not established.
xylene (1330-20-7)	
Bioaccumulative potential	Not established.
2-methoxy-1-methylethyl acetate (108-65-6)	
Partition coefficient n-octanol/water (Log Pow)	0,36
Partition coefficient n-octanol/water (Log Kow)	0,43
Bioaccumulative potential	Not established.
(none available)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecological information : Avoid release to the environment.




SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioaccumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : xylene is listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Gas 1A	Flammable gases, Category 1A

801801 - TOP AUTOMATIQUE BLANC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Diss.)	Gases under pressure : Dissolved gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge from information from our raw material suppliers and describes the product for health, safety and environmental purposes only. They should therefore not be interpreted as guaranteeing any specific property of the product. This information does not exempt the user from checking the product and in no way engages our responsibility as to the use for which it is intended.

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/06/2023 Revision date: 19/08/2024 Supersedes version of: 09/11/2023 Version: 6.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 801802 - TOP AUTOMATIQUE JAUNE
Product code : 801802
Type of product : Aerosol, Paints
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Spraytec
42, rue Gallieni
FR F-92600 Asnières sur Seine
France
T +33(0)1.40.80.32.32, F +33(0)1.40.80.32.30
infofds@itwpc.com, www.itwpc.com

Distributor

ROCOL a division of ITW Ltd
ROCOL House
Wakefield Rd, Swillington
UK LS26 8BS Leeds
United Kingdom
T +44 (0)113 232 2600
customer.service@rocol.com, www.rocol.com

1.4. Emergency telephone number

Emergency number : FRANCE :+ 33 (0)1 45 42 59 59

Country/Area	Organisation/Company	Address	Emergency number	Comment
Austria	Vergiftungsinformationszentrale	Stubenring 6 1010 Vienna	+43 1 406 43 43	
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Bulgaria	Национален токсикологичен информационен център Многопрофилна болница за активно лечение и спешна медицина "Н.И.Пирогов"	бул. Ген. Едуард И. Тотлебен 21 1606 Sofia	+359 2 9154 233	The phone is active 24/7 and calls to it are free
Croatia	Centar za kontrolu otrovanja Institut za medicinska istraživanja i medicinu rada	Ksaverska Cesta 2 p.p. 291 10000 Zagreb	+385 1 234 8342	Information available 24/7 in Croatian and English
Cyprus	Κέντρου Δηλητηριάσεων	Nicosia	1401	Operating hours 24 hours / 24 hours, 7 days a week

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Czech Republic	Toxikologické informační středisko Klinika pracovního lékařství VFN a 1. LF UK	Na Bojišti 1 120 00 Prague	+420 224 919 293 +420 224 915 402	and only in the event of a malfunction, phone 725 103 658 (otherwise there may not be a toxicologist on this phone!) Questions about ACUTE INTOXICATION of people and animals are dealt with exclusively on TIS direct telephone lines 24 hours a day
Denmark	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23E Opgang 20 C 2400 Copenhagen	+45 82 12 12 12	
Estonia	Mürgistusteabekeskus Terviseamet	Paldiski mnt 81 10614	16662 +372 7943 794	Calling the hotline is anonymous and at the cost of a local call.
Finland	Myrkytystietokeskus	Stenbäckinkatu 9 PO BOX 100 00029 Helsinki	+358 800 147 111 +358 9 471 977	Open 24 hours a day 0800 147 111 (free of charge) 09 471 977 (normal rate call)
Germany	BfR Bundesinstitut für Risikobewertung / German Federal Institute for Risk Assessment	Max-Dohrn-Str. 8-10 10589 Berlin	+49-30-18412-0	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Latvia	Valsts ugunsdzēsības un glābšanas dienests Toksikoloģijas un sepses klīnikas Saindēšanās un zāļu informācijas centrs	Hipokrāta 2 1038 Riga	112 +371 67 04 24 73	works 24 hours a day
Lithuania	Apsinuodijimų informacijos biuras	Šiltnamių g. 29 04130 Vilnius	+370 (5) 236 20 52	
Luxembourg	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, Dutch and English
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)
Norway	Giftinformasjonen	Folkehelseinstituttet Postboks 222 Skøyen 0213 Oslo	+47 22 59 13 00	Operating hours 24 hours / 24 hours, 7 days a week

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Poland	Szpital Praski p.w. Przemienienia Pańskiego Sp. z o.o.	Aleja Solidarności 67 03-401 Warsaw	+48 22 619 66 54 +48 22 619 08 97	
Portugal	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica	Rua Almirante Barroso, 36 1000-013	+351 800 250 250	
Romania	TOXAPEL Spitalul Clinic de Urgenta pentru Copii „Grigore Alexandrescu”	Boulevardul Iancu de Hunedoara 30-32 Bucharest	+40 2121 06282 +40 2121 06183	
Slovakia	Národné toxikologické informačné centrum Univerzitná nemocnica Bratislava, pracovisko Kramáre, Klinika pracovného lekárstva a toxikológie	Limbová 5 833 05 Bratislava	+421 2 54 77 41 66 +421 911 166 066	
Slovenia	Center za klinično toksikologijo in farmakologijo Univerzitetni klinični, Center Ljubljana	Zaloška 7 1000 Ljubljana	112	
Spain	Servicio de Información Toxicológica Instituto Nacional de Toxicología y Ciencias Forenses, Departamento de Madrid	C/José Echegaray nº4 28232 Las Rozas de Madrid	+34 91 562 04 20 +34 91 411 26 76 (teléfono solo para médicos)	(Toxicological emergencies only). Information in Spanish (24/7)
Sweden	Giftinformationscentralen	Solna Strandväg 21 171 54 Solna	112 – begär Giftinformation	
Switzerland	Tox Info Suisse	Freiestrasse 16 8032 Zürich	145 +41 44 251 51 51	(from abroad: +41 44 251 51 51) non urgent inquiry: +41 44 251 66 66
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

801802 - TOP AUTOMATIQUE JAUNE


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : Acetone; Hydrocarbons, C6, isoalkanes, <5% n-hexane; propan-2-ol; isopropyl alcohol; isopropanol; n-butyl acetate
- : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (containing < 0,1 % butadiene (203-450-8)) (Propellant gas (Aerosol)) (Note C)(Note U)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	10 – 30	Flam. Gas 1, H220 Aerosol 1, H222;H229 Press. Gas (Diss.), H280
Acetone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	< 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6, isoalkanes, <5% n-hexane (Note P)	CAS-No.: 64742-49-0 EC-No.: 931-254-9 EC Index-No.: 649-328-00-1 REACH-no: 01-2119484651-34	< 15	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propane (Propellant gas (Aerosol)) (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	< 15	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
Carbon dioxide (Propellant gas (Aerosol))	CAS-No.: 124-38-9 EC-No.: 204-696-9	< 10	Press. Gas (Comp.), H280
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	< 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
	CAS-No.: none available EC-No.: 920-750-0 REACH-no: 01-2119473851-33	< 10	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a POISON CENTER/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a POISON CENTER/doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking. Causes skin irritation.
Symptoms/effects after eye contact	: Eye irritation. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water haze. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Thermal decomposition generates : fume. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel.
----------------------	---

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Heat sources. Sources of ignition. Direct sunlight.
- Storage temperature : < 50 °C

Switzerland

- Storage class (LK) : LK 2 - Liquefied or pressurized gases

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
France - Occupational Exposure Limits	
Local name	n-Butane
VME (OEL TWA)	1900 mg/m ³
	800 ppm

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA)	1450 mg/m ³
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
	750 ppm
Remark	Carc. (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon dioxide (124-38-9)	
France - Occupational Exposure Limits	
Local name	Carbone (dioxyde de)
VME (OEL TWA)	9000 mg/m ³
	5000 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrêté du 26 octobre 2007)
United Kingdom - Occupational Exposure Limits	
Local name	Carbon dioxide
WEL TWA (OEL TWA)	9150 mg/m ³
	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m ³
	15000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Acetone (67-64-1)	
France - Occupational Exposure Limits	
Local name	Acétone
VME (OEL TWA)	1210 mg/m ³
	500 ppm
VLE (OEL C/STEL)	2420 mg/m ³
	1000 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acetone (67-64-1)	
WEL STEL (OEL STEL)	3620 mg/m ³
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
France - Occupational Exposure Limits	
Local name	propane-2-ol, alcool isopropylique, isopropanol
VLE (OEL C/STEL)	980 mg/m ³
	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-Propanol, Isopropylalkohol, Isopropanol
AGW (OEL TWA)	500 mg/m ³
	200 ppm
AGW (OEL C)	1000 mg/m ³
AGW (OEL C) [ppm]	400 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m ³
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
France - Occupational Exposure Limits	
Local name	Acétate de n-butyle
VME (OEL TWA)	710 mg/m ³
	150 ppm
VLE (OEL C/STEL)	940 mg/m ³
	200 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	n-Butylacetat
AGW (OEL TWA)	300 mg/m ³
	62 ppm
AGW (OEL C)	600 mg/m ³
AGW (OEL C) [ppm]	124 ppm

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m ³
	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
xylene (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene, o-,m-,p- or mixed isomers
WEL TWA (OEL TWA)	220 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
	100 ppm
Remark	Sk, BMGV
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

In case of repeated or prolonged contact wear gloves. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent). The choice of appropriate gloves depends not only on the material, but also on other quality criteria that may vary from one manufacturer to another. As the product is a preparation made from several substances, glove material resistance may not be calculated in advance and must be tested before use. The exact penetration time of glove material is to be determined by the manufacturer of protective gloves and respected. Wear protective gloves.

Other skin protection**Materials for protective clothing:**

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: Organic solvent.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: < 0 °C
Flammability	: Extremely flammable aerosol, Non flammable.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 0 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: soluble in most organic solvents. insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,9 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 79,965 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

None under normal conditions. Not established.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	≈ 76 mg/l/4h
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LD50 oral rat	> 36750 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 3350 ml/kg
LC50 Inhalation - Rat	259354 mg/l/4h
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg Source: ECHA
LD50 dermal rabbit	12800 mg/kg Source: ECHA

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 Inhalation - Rat	23,4 mg/l/4h
LC50 Inhalation - Rat (Vapours)	1802 mg/l Source: ECHA
(none available)	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
Additional information	: Repeated exposure may cause skin dryness or cracking.
Carbon dioxide (124-38-9)	
pH	3,2 Source: HSDB
Acetone (67-64-1)	
pH	5 Source: ECHA
n-butyl acetate (123-86-4)	
pH	6,2
Serious eye damage/irritation	: Causes serious eye irritation.
Carbon dioxide (124-38-9)	
pH	3,2 Source: HSDB
Acetone (67-64-1)	
pH	5 Source: ECHA
n-butyl acetate (123-86-4)	
pH	6,2
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
(none available)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LOAEC (inhalation, rat, vapour, 90 days)	16,6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapour, 90 days)	3,3 mg/l air Animal: rat, Animal sex: male
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
xylene (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
(none available)	
NOAEC (inhalation, rat, vapour, 90 days)	24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
801802 - TOP AUTOMATIQUE JAUNE	
Vaporizer	Aerosol
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Vaporizer	Aerosol
Acetone (67-64-1)	
Viscosity, kinematic	0,417 mm ² /s
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Viscosity, kinematic	0,46 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0,83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
xylene (1330-20-7)	
Viscosity, kinematic	< 0,9 mm ² /s
(none available)	
Viscosity, kinematic	0,715 – 0,786 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Ecology - water : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Carbon dioxide (124-38-9)

LC50 - Fish [1]	35 mg/l Source: HSDB
-----------------	----------------------

Acetone (67-64-1)

LC50 - Fish [1]	5540 – 11000 mg/l
-----------------	-------------------

EC50 - Crustacea [1]	8800 mg/l
----------------------	-----------

LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic algae	430 mg/l
--------------------	----------

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)

LC50 - Fish [1]	> 1 mg/l
-----------------	----------

LC50 - Other aquatic organisms [1]	2,6 mg/l Source: IUCLID
------------------------------------	-------------------------

EC50 - Crustacea [1]	3,87 mg/l
----------------------	-----------

ErC50 algae	30 mg/l
-------------	---------

LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

LC50 - Fish [1]	9640 mg/l Source: ECHA
-----------------	------------------------

LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
-----------------	---

n-butyl acetate (123-86-4)

LC50 - Fish [1]	18 mg/l
-----------------	---------

EC50 - Crustacea [1]	44 mg/l
----------------------	---------

EC50 72h - Algae [1]	674,7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
----------------------	---

EC50 72h - Algae [2]	246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
----------------------	--

ErC50 algae	647,7 mg/l
-------------	------------

LOEC (chronic)	47,6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic algae	200 mg/l
--------------------	----------

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(none available)	
LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

801802 - TOP AUTOMATIQUE JAUNE	
Persistence and degradability	May cause long-term adverse effects in the environment.
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Persistence and degradability	Rapidly degradable
Carbon dioxide (124-38-9)	
Persistence and degradability	Not established.
Propane (74-98-6)	
Persistence and degradability	Rapidly degradable
Acetone (67-64-1)	
Persistence and degradability	Not established.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Persistence and degradability	May cause long-term adverse effects in the environment.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Persistence and degradability	Not established.
n-butyl acetate (123-86-4)	
Persistence and degradability	Not established.
xylene (1330-20-7)	
Persistence and degradability	Not established.
(none available)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

801802 - TOP AUTOMATIQUE JAUNE	
Bioaccumulative potential	Not established.
Carbon dioxide (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0,83
Bioaccumulative potential	Not established.
Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0,24 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-0,24
Bioaccumulative potential	Not established.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Partition coefficient n-octanol/water (Log Pow)	2,1 – 6 Source: IUCLID

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Partition coefficient n-octanol/water (Log Kow)	4
Bioaccumulative potential	Not established.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0,05 Source: ICSC
Bioaccumulative potential	Not established.
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1,78 Source: HSDB
Partition coefficient n-octanol/water (Log Kow)	2,3
Bioaccumulative potential	Not established.
xylene (1330-20-7)	
Bioaccumulative potential	Not established.
(none available)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecological information : Avoid release to the environment.

SECTION 14: Transport information




In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
Transport document description		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioacumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : xylene is listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.

801802 - TOP AUTOMATIQUE JAUNE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Diss.)	Gases under pressure : Dissolved gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge from information from our raw material suppliers and describes the product for health, safety and environmental purposes only. They should therefore not be interpreted as guaranteeing any specific property of the product. This information does not exempt the user from checking the product and in no way engages our responsibility as to the use for which it is intended.

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/06/2023 Revision date: 19/08/2024 Supersedes version of: 09/11/2023 Version: 6.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 801803 - TOP AUTOMATIQUE ROUGE
Product code : 801803
Type of product : Aerosol, Paints
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

ITW Spraytec
42, rue Gallieni
FR F-92600 Asnières sur Seine
France
T +33(0)1.40.80.32.32, F +33(0)1.40.80.32.30
infofds@itwpc.com, www.itwpc.com

Distributor

ROCOL a division of ITW Ltd
ROCOL House
Wakefield Rd, Swillington
UK LS26 8BS Leeds
United Kingdom
T +44 (0)113 232 2600
customer.service@rocol.com, www.rocol.com

1.4. Emergency telephone number

Emergency number : FRANCE :+ 33 (0)1 45 42 59 59

Country/Area	Organisation/Company	Address	Emergency number	Comment
Austria	Vergiftungsinformationszentrale	Stubenring 6 1010 Vienna	+43 1 406 43 43	
Belgium	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Bulgaria	Национален токсикологичен информационен център Многопрофилна болница за активно лечение и спешна медицина "Н.И.Пирогов"	бул. Ген. Едуард И. Тотлебен 21 1606 Sofia	+359 2 9154 233	The phone is active 24/7 and calls to it are free
Croatia	Centar za kontrolu otrovanja Institut za medicinska istraživanja i medicinu rada	Ksaverska Cesta 2 p.p. 291 10000 Zagreb	+385 1 234 8342	Information available 24/7 in Croatian and English
Cyprus	Κέντρου Δηλητηριάσεων	Nicosia	1401	Operating hours 24 hours / 24 hours, 7 days a week

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Czech Republic	Toxikologické informační středisko Klinika pracovního lékařství VFN a 1. LF UK	Na Bojišti 1 120 00 Prague	+420 224 919 293 +420 224 915 402	and only in the event of a malfunction, phone 725 103 658 (otherwise there may not be a toxicologist on this phone!) Questions about ACUTE INTOXICATION of people and animals are dealt with exclusively on TIS direct telephone lines 24 hours a day
Denmark	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23E Opgang 20 C 2400 Copenhagen	+45 82 12 12 12	
Estonia	Mürgistusteabekeskus Terviseamet	Paldiski mnt 81 10614	16662 +372 7943 794	Calling the hotline is anonymous and at the cost of a local call.
Finland	Myrkytystietokeskus	Stenbäckinkatu 9 PO BOX 100 00029 Helsinki	+358 800 147 111 +358 9 471 977	Open 24 hours a day 0800 147 111 (free of charge) 09 471 977 (normal rate call)
Germany	BfR Bundesinstitut für Risikobewertung / German Federal Institute for Risk Assessment	Max-Dohrn-Str. 8-10 10589 Berlin	+49-30-18412-0	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Latvia	Valsts ugunsdzēsības un glābšanas dienests Toksikoloģijas un sepses klīnikas Saindēšanās un zāļu informācijas centrs	Hipokrāta 2 1038 Riga	112 +371 67 04 24 73	works 24 hours a day
Lithuania	Apsinuodijimų informacijos biuras	Šiltnamių g. 29 04130 Vilnius	+370 (5) 236 20 52	
Luxembourg	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, Dutch and English
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)
Norway	Giftinformasjonen	Folkehelseinstituttet Postboks 222 Skøyen 0213 Oslo	+47 22 59 13 00	Operating hours 24 hours / 24 hours, 7 days a week

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Poland	Szpital Praski p.w. Przemienienia Pańskiego Sp. z o.o.	Aleja Solidarności 67 03-401 Warsaw	+48 22 619 66 54 +48 22 619 08 97	
Portugal	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica	Rua Almirante Barroso, 36 1000-013	+351 800 250 250	
Romania	TOXAPEL Spitalul Clinic de Urgenta pentru Copii „Grigore Alexandrescu”	Boulevardul Iancu de Hunedoara 30-32 Bucharest	+40 2121 06282 +40 2121 06183	
Slovakia	Národné toxikologické informačné centrum Univerzitná nemocnica Bratislava, pracovisko Kramáre, Klinika pracovného lekárstva a toxikológie	Limbová 5 833 05 Bratislava	+421 2 54 77 41 66 +421 911 166 066	
Slovenia	Center za klinično toksikologijo in farmakologijo Univerzitetni klinični, Center Ljubljana	Zaloška 7 1000 Ljubljana	112	
Spain	Servicio de Información Toxicológica Instituto Nacional de Toxicología y Ciencias Forenses, Departamento de Madrid	C/José Echegaray nº4 28232 Las Rozas de Madrid	+34 91 562 04 20 +34 91 411 26 76 (teléfono solo para médicos)	(Toxicological emergencies only). Information in Spanish (24/7)
Sweden	Giftinformationscentralen	Solna Strandväg 21 171 54 Solna	112 – begär Giftinformation	
Switzerland	Tox Info Suisse	Freiestrasse 16 8032 Zürich	145 +41 44 251 51 51	(from abroad: +41 44 251 51 51) non urgent inquiry: +41 44 251 66 66
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

801803 - TOP AUTOMATIQUE ROUGE


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : n-butyl acetate; Hydrocarbons, C6, isoalkanes, <5% n-hexane; Acetone; propan-2-ol; isopropyl alcohol; isopropanol
- : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F, 50 °C.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (containing < 0,1 % butadiene (203-450-8)) (Propellant gas (Aerosol)) (Note C)(Note U)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	15 - 35	Flam. Gas 1, H220 Aerosol 1, H222;H229 Press. Gas (Diss.), H280
Propane (Propellant gas (Aerosol)) (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	< 15	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
	CAS-No.: none available EC-No.: 920-750-0 REACH-no: 01-2119473851-33	< 10	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
Acetone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	< 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Hydrocarbons, C6, isoalkanes, <5% n-hexane (Note P)	CAS-No.: 64742-49-0 EC-No.: 931-254-9 EC Index-No.: 649-328-00-1 REACH-no: 01-2119484651-34	< 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	< 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Carbon dioxide (Propellant gas (Aerosol))	CAS-No.: 124-38-9 EC-No.: 204-696-9	< 5	Press. Gas (Comp.), H280
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a POISON CENTER/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a POISON CENTER/doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking. Causes skin irritation.
Symptoms/effects after eye contact	: Eye irritation. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water haze. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Thermal decomposition generates : fume. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel.
----------------------	---

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Heat sources. Sources of ignition. Direct sunlight.
- Storage temperature : < 50 °C

Switzerland

- Storage class (LK) : LK 2 - Liquefied or pressurized gases

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
France - Occupational Exposure Limits	
Local name	n-Butane
VME (OEL TWA)	1900 mg/m ³
	800 ppm

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA)	1450 mg/m ³
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
	750 ppm
Remark	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon dioxide (124-38-9)	
France - Occupational Exposure Limits	
Local name	Carbone (dioxyde de)
VME (OEL TWA)	9000 mg/m ³
	5000 ppm
Remark	Valeurs règlementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrêté du 26 octobre 2007)
United Kingdom - Occupational Exposure Limits	
Local name	Carbon dioxide
WEL TWA (OEL TWA)	9150 mg/m ³
	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m ³
	15000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
xylene (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene, o-,m-,p- or mixed isomers
WEL TWA (OEL TWA)	220 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
	100 ppm
Remark	Sk, BMGV
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
France - Occupational Exposure Limits	
Local name	Acétate de n-butyle
VME (OEL TWA)	710 mg/m ³
	150 ppm
VLE (OEL C/STEL)	940 mg/m ³
	200 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	n-Butylacetat
AGW (OEL TWA)	300 mg/m ³
	62 ppm
AGW (OEL C)	600 mg/m ³
AGW (OEL C) [ppm]	124 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m ³
	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Acetone (67-64-1)	
France - Occupational Exposure Limits	
Local name	Acétone
VME (OEL TWA)	1210 mg/m ³
	500 ppm
VLE (OEL C/STEL)	2420 mg/m ³
	1000 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

France - Occupational Exposure Limits

Local name	propane-2-ol, alcool isopropylique, isopropanol
VLE (OEL C/STEL)	980 mg/m ³ 400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)

Germany - Occupational Exposure Limits (TRGS 900)

Local name	2-Propanol, Isopropylalkohol, Isopropanol
AGW (OEL TWA)	500 mg/m ³ 200 ppm
AGW (OEL C)	1000 mg/m ³
AGW (OEL C) [ppm]	400 ppm

United Kingdom - Occupational Exposure Limits

Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m ³ 400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³ 500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. Chemical goggles or safety glasses

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

In case of repeated or prolonged contact wear gloves. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent). The choice of appropriate gloves depends not only on the material, but also on other quality criteria that may vary from one manufacturer to another. As the product is a preparation made from several substances, glove material resistance may not be calculated in advance and must be tested before use. The exact penetration time of glove material is to be determined by the manufacturer of protective gloves and respected. Wear protective gloves.

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: Organic solvent.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: < 0 °C
Flammability	: Extremely flammable aerosol, Non flammable.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 0 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: soluble in most organic solvents. insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,914 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 77,68861 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

None under normal conditions. Not established.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

(none available)

LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

n-butyl acetate (123-86-4)

LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 Inhalation - Rat	23,4 mg/l/4h
LC50 Inhalation - Rat (Vapours)	1802 mg/l Source: ECHA

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)

LD50 oral rat	> 36750 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 3350 ml/kg
LC50 Inhalation - Rat	259354 mg/l/4h
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	≈ 76 mg/l/4h
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg Source: ECHA
LD50 dermal rabbit	12800 mg/kg Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.
Additional information	: Repeated exposure may cause skin dryness or cracking.
Carbon dioxide (124-38-9)	
pH	3,2 Source: HSDB
n-butyl acetate (123-86-4)	
pH	6,2
Acetone (67-64-1)	
pH	5 Source: ECHA
Serious eye damage/irritation	: Causes serious eye irritation.
Carbon dioxide (124-38-9)	
pH	3,2 Source: HSDB
n-butyl acetate (123-86-4)	
pH	6,2
Acetone (67-64-1)	
pH	5 Source: ECHA
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
(none available)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
xylene (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
(none available)	
NOAEC (inhalation, rat, vapour, 90 days)	24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LOAEC (inhalation, rat, vapour, 90 days)	16,6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapour, 90 days)	3,3 mg/l air Animal: rat, Animal sex: male
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
801803 - TOP AUTOMATIQUE ROUGE	
Vaporizer	Aerosol
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Vaporizer	Aerosol
xylene (1330-20-7)	
Viscosity, kinematic	< 0,9 mm ² /s
(none available)	
Viscosity, kinematic	0,715 – 0,786 mm ² /s Temp.: 'other.' Parameter: 'kinematic viscosity (in mm ² /s)'
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0,83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Viscosity, kinematic	0,46 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Acetone (67-64-1)	
Viscosity, kinematic	0,417 mm ² /s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Ecology - water : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Carbon dioxide (124-38-9)

LC50 - Fish [1]	35 mg/l Source: HSDB
-----------------	----------------------

(none available)

LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

n-butyl acetate (123-86-4)

LC50 - Fish [1]	18 mg/l
-----------------	---------

EC50 - Crustacea [1]	44 mg/l
----------------------	---------

EC50 72h - Algae [1]	674,7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
----------------------	---

EC50 72h - Algae [2]	246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
----------------------	--

ErC50 algae	647,7 mg/l
-------------	------------

LOEC (chronic)	47,6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic algae	200 mg/l
--------------------	----------

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)

LC50 - Fish [1]	> 1 mg/l
-----------------	----------

LC50 - Other aquatic organisms [1]	2,6 mg/l Source: IUCLID
------------------------------------	-------------------------

EC50 - Crustacea [1]	3,87 mg/l
----------------------	-----------

ErC50 algae	30 mg/l
-------------	---------

LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

Acetone (67-64-1)

LC50 - Fish [1]	5540 – 11000 mg/l
-----------------	-------------------

EC50 - Crustacea [1]	8800 mg/l
----------------------	-----------

LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic algae	430 mg/l
--------------------	----------

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LC50 - Fish [1]	9640 mg/l Source: ECHA
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

12.2. Persistence and degradability

801803 - TOP AUTOMATIQUE ROUGE	
Persistence and degradability	May cause long-term adverse effects in the environment.
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Persistence and degradability	Rapidly degradable
Propane (74-98-6)	
Persistence and degradability	Rapidly degradable
Carbon dioxide (124-38-9)	
Persistence and degradability	Not established.
xylene (1330-20-7)	
Persistence and degradability	Not established.
(none available)	
Persistence and degradability	May cause long-term adverse effects in the environment.
n-butyl acetate (123-86-4)	
Persistence and degradability	Not established.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Acetone (67-64-1)	
Persistence and degradability	Not established.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

801803 - TOP AUTOMATIQUE ROUGE	
Bioaccumulative potential	Not established.
Carbon dioxide (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0,83
Bioaccumulative potential	Not established.
xylene (1330-20-7)	
Bioaccumulative potential	Not established.
(none available)	
Bioaccumulative potential	Not established.
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1,78 Source: HSDB

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Kow)	2,3
Bioaccumulative potential	Not established.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Partition coefficient n-octanol/water (Log Pow)	2,1 – 6 Source: IUCLID
Partition coefficient n-octanol/water (Log Kow)	4
Bioaccumulative potential	Not established.
Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0,24 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-0,24
Bioaccumulative potential	Not established.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0,05 Source: ICSC
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecological information : Avoid release to the environment.

SECTION 14: Transport information




In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
Transport document description		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germany

- Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Chemicals Prohibition Ordinance (ChemVerbotsV) : This product is subject to ChemVerbotsV Annex 1 Entry 1. Paragraph 1) Coated and uncoated wood-based materials (chipboard, blockboard, veneer panels, and fibreboard) may not be placed on the market if the equalizing concentration of formaldehyde in the air in a test room exceeds 0.1 ml / cbm (ppm). Paragraph 2) Furniture that contains wood-based materials that do not meet the requirements of Paragraph 1 may not be placed on the market. Paragraph 1 is also deemed to have been fulfilled if the furniture complies with the equalization concentration specified in paragraph 1 during a whole-body test. Paragraph 3) Detergents, cleaning agents and care products with a mass content of more than 0.2% formaldehyde may not be placed on the market.
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

- ABM category : Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioacumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : xylene is listed

Denmark

- Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes version of	Modified	
	Revision date	Modified	
	Display additional SDS EU addresses	Added	

- Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

- Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

801803 - TOP AUTOMATIQUE ROUGE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Diss.)	Gases under pressure : Dissolved gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge from information from our raw material suppliers and describes the product for health, safety and environmental purposes only. They should therefore not be interpreted as guaranteeing any specific property of the product. This information does not exempt the user from checking the product and in no way engages our responsibility as to the use for which it is intended.

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/06/2023 Revision date: 19/08/2024 Supersedes version of: 09/11/2023 Version: 6.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 801806 - TOP AUTOMATIQUE BLEU
Product code : 801806
Type of product : Aerosol, Paints
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Spraytec
42, rue Gallieni
FR F-92600 Asnières sur Seine
France
T +33(0)1.40.80.32.32, F +33(0)1.40.80.32.30
infofds@itwpc.com, www.itwpc.com

Distributor

ROCOL a division of ITW Ltd
ROCOL House
Wakefield Rd, Swillington
UK LS26 8BS Leeds
United Kingdom
T +44 (0)113 232 2600
customer.service@rocol.com, www.rocol.com

1.4. Emergency telephone number

Emergency number : FRANCE :+ 33 (0)1 45 42 59 59

Country/Area	Organisation/Company	Address	Emergency number	Comment
Austria	Vergiftungsinformationszentrale	Stubenring 6 1010 Vienna	+43 1 406 43 43	
Belgium	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Bulgaria	Национален токсикологичен информационен център Многопрофилна болница за активно лечение и спешна медицина "Н.И.Пирогов"	бул. Ген. Едуард И. Тотлебен 21 1606 Sofia	+359 2 9154 233	The phone is active 24/7 and calls to it are free
Croatia	Centar za kontrolu otrovanja Institut za medicinska istraživanja i medicinu rada	Ksaverska Cesta 2 p.p. 291 10000 Zagreb	+385 1 234 8342	Information available 24/7 in Croatian and English
Cyprus	Κέντρου Δηλητηριάσεων	Nicosia	1401	Operating hours 24 hours / 24 hours, 7 days a week

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Czech Republic	Toxikologické informační středisko Klinika pracovního lékařství VFN a 1. LF UK	Na Bojišti 1 120 00 Prague	+420 224 919 293 +420 224 915 402	and only in the event of a malfunction, phone 725 103 658 (otherwise there may not be a toxicologist on this phone!) Questions about ACUTE INTOXICATION of people and animals are dealt with exclusively on TIS direct telephone lines 24 hours a day
Denmark	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23E Opgang 20 C 2400 Copenhagen	+45 82 12 12 12	
Estonia	Mürgistusteabekeskus Terviseamet	Paldiski mnt 81 10614	16662 +372 7943 794	Calling the hotline is anonymous and at the cost of a local call.
Finland	Myrkytystietokeskus	Stenbäckinkatu 9 PO BOX 100 00029 Helsinki	+358 800 147 111 +358 9 471 977	Open 24 hours a day 0800 147 111 (free of charge) 09 471 977 (normal rate call)
Germany	BfR Bundesinstitut für Risikobewertung / German Federal Institute for Risk Assessment	Max-Dohrn-Str. 8-10 10589 Berlin	+49-30-18412-0	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Latvia	Valsts ugunsdzēsības un glābšanas dienests Toksikoloģijas un sepses klīnikas Saindēšanās un zāļu informācijas centrs	Hipokrāta 2 1038 Riga	112 +371 67 04 24 73	works 24 hours a day
Lithuania	Apsinuodijimų informacijos biuras	Šiltnamių g. 29 04130 Vilnius	+370 (5) 236 20 52	
Luxembourg	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, Dutch and English
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)
Norway	Giftinformasjonen	Folkehelseinstituttet Postboks 222 Skøyen 0213 Oslo	+47 22 59 13 00	Operating hours 24 hours / 24 hours, 7 days a week

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Country/Area	Organisation/Company	Address	Emergency number	Comment
Poland	Szpital Praski p.w. Przemienienia Pańskiego Sp. z o.o.	Aleja Solidarności 67 03-401 Warsaw	+48 22 619 66 54 +48 22 619 08 97	
Portugal	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica	Rua Almirante Barroso, 36 1000-013	+351 800 250 250	
Romania	TOXAPEL Spitalul Clinic de Urgenta pentru Copii „Grigore Alexandrescu”	Boulevardul Iancu de Hunedoara 30-32 Bucharest	+40 2121 06282 +40 2121 06183	
Slovakia	Národné toxikologické informačné centrum Univerzitná nemocnica Bratislava, pracovisko Kramáre, Klinika pracovného lekárstva a toxikológie	Limbová 5 833 05 Bratislava	+421 2 54 77 41 66 +421 911 166 066	
Slovenia	Center za klinično toksikologijo in farmakologijo Univerzitetni klinični, Center Ljubljana	Zaloška 7 1000 Ljubljana	112	
Spain	Servicio de Información Toxicológica Instituto Nacional de Toxicología y Ciencias Forenses, Departamento de Madrid	C/José Echegaray nº4 28232 Las Rozas de Madrid	+34 91 562 04 20 +34 91 411 26 76 (teléfono solo para médicos)	(Toxicological emergencies only). Information in Spanish (24/7)
Sweden	Giftinformationscentralen	Solna Strandväg 21 171 54 Solna	112 – begär Giftinformation	
Switzerland	Tox Info Suisse	Freiestrasse 16 8032 Zürich	145 +41 44 251 51 51	(from abroad: +41 44 251 51 51) non urgent inquiry: +41 44 251 66 66
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

801806 - TOP AUTOMATIQUE BLEU


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : Acetone
- : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (containing < 0,1 % butadiene (203-450-8)) (Propellant gas (Aerosol)) (Note C)(Note U)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	10 – 30	Flam. Gas 1, H220 Aerosol 1, H222;H229 Press. Gas (Diss.), H280
Propane (Propellant gas (Aerosol)) (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	< 15	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	< 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Hydrocarbons, C6, isoalkanes, <5% n-hexane (Note P)	CAS-No.: 64742-49-0 EC-No.: 931-254-9 EC Index-No.: 649-328-00-1 REACH-no: 01-2119484651-34	< 15	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Carbon dioxide (Propellant gas (Aerosol))	CAS-No.: 124-38-9 EC-No.: 204-696-9	< 10	Press. Gas (Comp.), H280
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	< 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
	CAS-No.: none available EC-No.: 920-750-0 REACH-no: 01-2119473851-33	< 10	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a POISON CENTER/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a POISON CENTER/doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking. Causes skin irritation.
Symptoms/effects after eye contact	: Eye irritation. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water haze. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Thermal decomposition generates : fume. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel.
----------------------	---

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Heat sources. Sources of ignition. Direct sunlight.
- Storage temperature : < 50 °C

Switzerland

- Storage class (LK) : LK 2 - Liquefied or pressurized gases

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
France - Occupational Exposure Limits	
Local name	n-Butane
VME (OEL TWA)	1900 mg/m ³
	800 ppm

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA)	1450 mg/m ³
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
	750 ppm
Remark	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon dioxide (124-38-9)	
France - Occupational Exposure Limits	
Local name	Carbone (dioxyde de)
VME (OEL TWA)	9000 mg/m ³
	5000 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrêté du 26 octobre 2007)
United Kingdom - Occupational Exposure Limits	
Local name	Carbon dioxide
WEL TWA (OEL TWA)	9150 mg/m ³
	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m ³
	15000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Acetone (67-64-1)	
France - Occupational Exposure Limits	
Local name	Acétone
VME (OEL TWA)	1210 mg/m ³
	500 ppm
VLE (OEL C/STEL)	2420 mg/m ³
	1000 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acetone (67-64-1)	
WEL STEL (OEL STEL)	3620 mg/m ³
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
France - Occupational Exposure Limits	
Local name	propane-2-ol, alcool isopropylique, isopropanol
VLE (OEL C/STEL)	980 mg/m ³
	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-Propanol, Isopropylalkohol, Isopropanol
AGW (OEL TWA)	500 mg/m ³
	200 ppm
AGW (OEL C)	1000 mg/m ³
AGW (OEL C) [ppm]	400 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m ³
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
France - Occupational Exposure Limits	
Local name	Acétate de n-butyle
VME (OEL TWA)	710 mg/m ³
	150 ppm
VLE (OEL C/STEL)	940 mg/m ³
	200 ppm
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 6443, 2022; Outil65; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	n-Butylacetat
AGW (OEL TWA)	300 mg/m ³
	62 ppm
AGW (OEL C)	600 mg/m ³
AGW (OEL C) [ppm]	124 ppm

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m ³
	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
xylene (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene, o-,m-,p- or mixed isomers
WEL TWA (OEL TWA)	220 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
	100 ppm
Remark	Sk, BMGV
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

In case of repeated or prolonged contact wear gloves. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent). The choice of appropriate gloves depends not only on the material, but also on other quality criteria that may vary from one manufacturer to another. As the product is a preparation made from several substances, glove material resistance may not be calculated in advance and must be tested before use. The exact penetration time of glove material is to be determined by the manufacturer of protective gloves and respected. Wear protective gloves.

Other skin protection**Materials for protective clothing:**

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: Organic solvent.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: < 0 °C
Flammability	: Extremely flammable aerosol, Non flammable.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 0 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: soluble in most organic solvents. insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,91 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 78,82 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

None under normal conditions. Not established.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	≈ 76 mg/l/4h
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LD50 oral rat	> 36750 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 3350 ml/kg
LC50 Inhalation - Rat	259354 mg/l/4h
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg Source: ECHA
LD50 dermal rabbit	12800 mg/kg Source: ECHA

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 Inhalation - Rat	23,4 mg/l/4h
LC50 Inhalation - Rat (Vapours)	1802 mg/l Source: ECHA
(none available)	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
Additional information	: Repeated exposure may cause skin dryness or cracking.
Carbon dioxide (124-38-9)	
pH	3,2 Source: HSDB
Acetone (67-64-1)	
pH	5 Source: ECHA
n-butyl acetate (123-86-4)	
pH	6,2
Serious eye damage/irritation	: Causes serious eye irritation.
Carbon dioxide (124-38-9)	
pH	3,2 Source: HSDB
Acetone (67-64-1)	
pH	5 Source: ECHA
n-butyl acetate (123-86-4)	
pH	6,2
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
(none available)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LOAEC (inhalation, rat, vapour, 90 days)	16,6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapour, 90 days)	3,3 mg/l air Animal: rat, Animal sex: male
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
xylene (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
(none available)	
NOAEC (inhalation, rat, vapour, 90 days)	24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
801806 - TOP AUTOMATIQUE BLEU	
Vaporizer	Aerosol
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Vaporizer	Aerosol
Acetone (67-64-1)	
Viscosity, kinematic	0,417 mm ² /s
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Viscosity, kinematic	0,46 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0,83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
xylene (1330-20-7)	
Viscosity, kinematic	< 0,9 mm ² /s
(none available)	
Viscosity, kinematic	0,715 – 0,786 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Ecology - water : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Carbon dioxide (124-38-9)

LC50 - Fish [1]	35 mg/l Source: HSDB
-----------------	----------------------

Acetone (67-64-1)

LC50 - Fish [1]	5540 – 11000 mg/l
-----------------	-------------------

EC50 - Crustacea [1]	8800 mg/l
----------------------	-----------

LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic algae	430 mg/l
--------------------	----------

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)

LC50 - Fish [1]	> 1 mg/l
-----------------	----------

LC50 - Other aquatic organisms [1]	2,6 mg/l Source: IUCLID
------------------------------------	-------------------------

EC50 - Crustacea [1]	3,87 mg/l
----------------------	-----------

ErC50 algae	30 mg/l
-------------	---------

LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

LC50 - Fish [1]	9640 mg/l Source: ECHA
-----------------	------------------------

LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
-----------------	---

n-butyl acetate (123-86-4)

LC50 - Fish [1]	18 mg/l
-----------------	---------

EC50 - Crustacea [1]	44 mg/l
----------------------	---------

EC50 72h - Algae [1]	674,7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
----------------------	---

EC50 72h - Algae [2]	246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
----------------------	--

ErC50 algae	647,7 mg/l
-------------	------------

LOEC (chronic)	47,6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic algae	200 mg/l
--------------------	----------

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(none available)	
LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

801806 - TOP AUTOMATIQUE BLEU	
Persistence and degradability	May cause long-term adverse effects in the environment.
butane (containing < 0,1 % butadiene (203-450-8)) (106-97-8)	
Persistence and degradability	Rapidly degradable
Propane (74-98-6)	
Persistence and degradability	Rapidly degradable
Carbon dioxide (124-38-9)	
Persistence and degradability	Not established.
Acetone (67-64-1)	
Persistence and degradability	Not established.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Persistence and degradability	May cause long-term adverse effects in the environment.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Persistence and degradability	Not established.
n-butyl acetate (123-86-4)	
Persistence and degradability	Not established.
xylene (1330-20-7)	
Persistence and degradability	Not established.
(none available)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

801806 - TOP AUTOMATIQUE BLEU	
Bioaccumulative potential	Not established.
Carbon dioxide (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0,83
Bioaccumulative potential	Not established.
Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0,24 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-0,24
Bioaccumulative potential	Not established.
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Partition coefficient n-octanol/water (Log Pow)	2,1 – 6 Source: IUCLID

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
Partition coefficient n-octanol/water (Log Kow)	4
Bioaccumulative potential	Not established.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0,05 Source: ICSC
Bioaccumulative potential	Not established.
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1,78 Source: HSDB
Partition coefficient n-octanol/water (Log Kow)	2,3
Bioaccumulative potential	Not established.
xylene (1330-20-7)	
Bioaccumulative potential	Not established.
(none available)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecological information : Avoid release to the environment.

SECTION 14: Transport information




In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
Transport document description		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioacumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : xylene is listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.

801806 - TOP AUTOMATIQUE BLEU

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Diss.)	Gases under pressure : Dissolved gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge from information from our raw material suppliers and describes the product for health, safety and environmental purposes only. They should therefore not be interpreted as guaranteeing any specific property of the product. This information does not exempt the user from checking the product and in no way engages our responsibility as to the use for which it is intended.