

## Chainguard 550

### High temperature graphited chain and conveyor lubricant

#### Product Overview

ROCOL® CHAINGUARD 550 is a graphite based high temperature, dry film chain lubricant specifically formulated for the lubrication of oven chains subjected to extremes of temperature up to 550°C.

ROCOL CHAINGUARD 550 is ideal for the lubrication of conveyor chains in high temperature environments where the risk of product contamination by a wet lubricant cannot be tolerated. For example, bakery oven chains, or where temperatures are too high for wet lubricants to be used.

#### Features and Benefits

- Temperature range:
  - Moist film - minus10°C to +180°C
  - Dry film up to +550°C
- ROCOL CHAINGUARD 550 should be applied below 120°C to achieve full penetration of the graphited lubricating solids.
- The base fluid evaporates cleanly, leaving no carbonised residues, as the oven is gradually brought up to full operating temperature.
- The product does not attract dust/dirt when operating as a dry film above 180°C.
- The dry film coating reduces issues of potential contamination commonly associated with wet chain lubricants.
- ROCOL CHAINGUARD 550 offers excellent EP and anti-wear properties at high temperature giving reduced wear and longer chain life.
- Low fuming provides a clean and safe working environment.

#### Directions for Storage and Use

- ROCOL CHAIN GUARD 550 is a heavy duty lubricant designed for manual application by pressure oilcan.
- It can also be brushed onto the chain, after the removal of any heavy deposits of dirt or grime.
- ROCOL CHAINGUARD 550 should be applied to a cool chain (less than 120°C), when the ovens are cooling down, to ensure adequate penetration before the clean evaporation of the base fluid as the oven returns to operating temperature.
- Product should be stored unopened in the original container between +1°C and +40°C.
- Agitate well before use and ensure product remains in suspension throughout use.
- If stored in accordance with the above guidelines, shelf life is 2 years from date of manufacture.

#### Typical Applications

Paint stoving ovens, bakery oven chains and other similar applications where extreme temperature and/or a dry film chain lubricant are required.

#### Pack Sizes

Pack Size	Part Code
5L	22076
20L	22075

## Chainguard 550

### High temperature graphited chain and conveyor lubricant

Property	Test Method	Result
Colour	Visual	Dark grey liquid
Base Oil Type	N/A	Polyalkylene glycol
Performance Additives:	N/A	Graphite
Graphite Content	N/A	15%
Graphite Particle Size	N/A	95% less than 10 micron
Temperature Range:		
Moist film	N/A	-10°C to +180°C
Dry film	N/A	+180°C to +550°C
Kinematic Viscosity:	ASTM D445	
cSt @ 40°C	IP 71	224
cSt @ 100°C	IP 71	36.7
Density (g/cm <sup>3</sup> )	N/A	1.1

Values quoted above are typical and do not constitute a specification.

### Safety Data Sheets

Safety data sheets are available for download from our website [www.rocol.com](http://www.rocol.com) or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 2 Date: 11-20

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTORS  
IN PEOPLE