



Ref	
Date	25/2/03
Issue No	
Page No	1 of 1

Non Slip Aggregate Technical Specification

Description

A high performance anti-slip aggregate having excellent impact and abrasion resistance. Recommended for use with the Cicol™ range of coatings.

Technical Data (Typical)

Description:	Natural, non-calcined, aluminium oxide
Shape:	Cubic/angular
Grades:	1.4-2.0 mm 1.0-3.0 mm 3.0-5.0 mm
Colour:	Dark grey/black
Physical properties in accordance with BS812:	
Aggregate Abrasion Value:	1.2
Aggregate Crushing Value:	7
Aggregate Impact Value:	6
Polished Stone value:	70
10% Fines Value:	565kN
Mohs Hardness:	9
Specific Gravity:	4

Health & Safety

The material is not classified as hazardous in accordance with Chemicals (Hazard Information and Packaging for Supply) regulations but we would recommend that when handling the material the following measures should be taken;

Wear suitable gloves & avoid inhaling dust

For further information please contact us at the address below:

ROCOL Site Safety Systems

ROCOL House, Swillington, Leeds, LS26 8BS, United Kingdom
Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2850 Technical Helpline: +44 (0)113 232 2840
www.rocol.com