

FOODLUBE® Spray

Food grade, multipurpose lubricant spray



Nonfood Compounds
H1 Registered
ISO 21469 Certified
NSF 537 PFAS-Free Certified

Description

FOODLUBE Spray is a non-toxic, food grade, multi-purpose maintenance product that penetrates, lubricates, displaces water and protects against corrosion. It is also suitable for use as a food-grade drilling, tapping and cutting lubricant particularly when maintenance is required in a process area.

It is ideal as a general, light, oily lubricant used to lubricate and protect many types of components such as linkages, pivots and pins commonly found in food, pharmaceutical and other clean environments.

It provides effective penetration, lubrication and protection for a wide variety of applications particularly those found in food, pharmaceutical and other clean environments.

Applications

- Links, pivots & pins
- Releasing lubricant
- Water displacing

Usage Guidance

Use in a well ventilated areas and ensure there are no sources of ignition.

Shake the FOODLUBE Spray thoroughly before use.

Apply FOODLUBE Spray from a distance of 15-30 cm (6-12 inches).

Pack Sizes

Part Code	Pack Size
15710	300 mL

Features and Benefits

- Excellent wide temperature resistance of -20°C to +110°C.
- Exhibits excellent water displacing and penetration properties ensuring optimum performance even when used on damp or wet components.
- Good load carrying capability with a long life, lubricating film.
- Provides excellent corrosion protection.
- Metal detectable plastic components (aerosol caps and actuators) capable of detection by most metal detection equipment.

Storage Guidance

The storage temperature should be kept below +50°C, and the storage area should be out of direct sunlight. Shelf life is 5 years from date of manufacture.

Approvals and Certifications

- NSF H1 registered - 121616
- ISO 21469
- NSF 537 - PFAS Free
- Halal certified
- Kosher certified
- Vegan Society Certified
- ROCOL unique TPM number - 12
- Manufactured from only FDA listed ingredients: FDA Group 21 CFR 178.3570
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.

T +44 (0) 113 232 2600

E customer.service@rocol.com

www.rocol.com

ROCOL A Division of ITW Limited

ROCOL House, Swillington, Leeds, LS26 8BS, UK

VAT Number: 742053167

Registered Company No: 00559693

Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN



FOODLUBE Spray

Food grade, multipurpose lubricant spray

Parameter	Test Method	Value
Appearance	Visual	Thin oily film
Base type	N/A	Blend of esters
Kinematic viscosity at 40 °C	IP 71 - ASTM D445	8 cSt
Solvent	N/A	None
Propellant	N/A	Carbon dioxide (CO ₂)
Odour	N/A	Characteristic
Temperature range - continuous	N/A	-20 °C to +110 °C
4-Ball weld load	IP 239 - ASTM D2596	180 kg
Metal detection;		
Aerosol cap	Equivalent sphere size	> 3.0 mm
Actuator	Equivalent sphere size	> 3.0 mm

Safety Datasheets

These are available at <https://www.rocol.com/datasheets>. For further assistance, please contact us via the ROCOL website or using the details below.

Note

The information in this Technical Datasheet is informed by our experience and feedback from industry. There are many variables outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. Values quoted are typical and do not constitute a specification.

If you'd like to discuss the suitability of any ROCOL solution for your system, please get in touch.

T +44 (0) 113 232 2600

E customer.service@rocol.com

www.rocol.com

ROCOL A Division of ITW Limited

ROCOL House, Swillington, Leeds, LS26 8BS, UK

VAT Number: 742053167

Registered Company No: 00559693

Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN

