

Technical Data

FOODLUBE® UNILUBE

Food grade, multipurpose, extreme pressure grease in automatic lubricator



Nonfood Compounds
Program Listed: H1
ISO 21469 Certified

Description

ROCOL® FOODLUBE UNILUBE is a gas operated automatic lubricator containing the high performance FOODLUBE Premier 1 grease.

ROCOL FOODLUBE Premier 1 is a soft, white, non-toxic grease designed for the effective lubrication and protection of ball, roller and plain bearings, slides and bushes particularly those operating in food, pharmaceutical and other clean environments.

FOODLUBE Premier 1 is an excellent all round NLGI No.1 grease offering excellent water wash off resistance and corrosion protection necessary for lubricants used in food, pharmaceutical and other clean environments.

Applications

- Ball Bearings
- Roller Bearings
- Plain Bearings
- Linear Bearings
- Slides
- Bushes
- Electric Motor Bearings

Approvals / Specifications

- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Manufactured from only FDA listed ingredients:
 - FDA Group 21 CFR 178.3570
- NSF H1 registered – 141084
- ISO 21469
- Halal certified
- Kosher certified
- Rocol unique TPM number – 43

Features & Benefits

- Offers an excellent wide temperature resistance of -30°C to +180°C
- Excellent EP performance with a 4-ball weld load of 315 kg.
- Highly resistant to water wash off and offers excellent corrosion protection.
- Excellent oxidation stability resulting in extended relubrication intervals and a reduction in lubricant usage.
- Excellent pumpability

Directions For Use

Prime the mounting point with FOODLUBE Premier 1 prior to fitting the FOODLUBE UNILUBE.

Screw the unit into ¼” BSP female fitting attached to the lubrication point.

The storage temperature should be controlled between +1°C and +40°C.

Shelf life is 3 years from date of manufacture.

Further Information

For pack sizes, part codes and safety data sheets please visit www.rocol.com or get in touch with our customer service team who will be happy to help: customer.service@rocol.com

Technical Data

FOODLUBE® AUTOLUBE

Food grade, multipurpose, extreme pressure grease in automatic lubricator



Nonfood Compounds Program Listed: H1
ISO 21469 Certified

Property	Test Method	Result
Appearance	Visual	White tenacious grease
NLGI No.	IP 50 - ASTM D217	1
Base Type	N/A	Polyalphaolefin
Base Fluid Viscosity at 40°C	IP71-ASTM D445	150cSt
Thickener	N/A	Complex soap
Solids	N/A	White, non-toxic solids
Temperature Range	N/A	-30°C to +180°C
UNILUBE Operating Range	N/A	-20°C to +60°C
4-Ball Weld Load	IP239-ASTM D2596	315kg
SKF-ROF Bearing Life	N/A	1390 hours
Corrosion Test-Emcor	IP 220	0:0
Copper Corrosion Test	IP112-ASTM D130	1b
Water Washout Test	IP215-ASTM D1264	<2%
Maximum UNILUBE Diameter	N/A	58mm
Maximum UNILUBE Length	N/A	117mm

Values quoted above are typical and do not constitute a specification.

Issue 6 Date: 02/24

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740
E customer.service@rocol.com www.rocol.com
ROCOL House, Swillington, Leeds LS26 8BS

ROCOL® A division of ITW Ltd

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.



Technical Data

TECHNICAL DATA FOR ROCOL FOODLUBE UNILUBE SPECIFICATIONS

- Supplied fully assembled and ready to use - no separate tools required
- Charge the lubrication point and any remote piping with the same lubricant as supplied in the UNILUBE
- Rotate the top of the UNILUBE to the required monthly frequency
 - Then tightly screw the UNILUBE, by hand, into an R1/4 (¼ BSP) female connection
- Do not remove the UNILUBE from its connection point once activated as the unit will lose pressure and will have to re-pressurise once it has been reinstalled
- The unit can be mounted remotely up to 1 metre away (horizontal to, or above, application point) with 6mm bore (8mm O.D.) nylon airline tubing. Reduce tube length to 0.5 metre if pumping uphill
- The ROCOL UNILUBE is a gas generated, disposable, automatic lubricator o Gas is generated by a sodium azide-free battery
- Ingress protection to IP 68
- ROCOL UNILUBE fitting – R1/4 (¼ BSP) male
- Dispensing;
 - Variable from 1 – 12 months in monthly increments - Settings can be altered during dispensing period
 - The unit can be switched off during dispensing period
 - Capacity – 125 ml - Non-refillable
 - Approximate sizes - Maximum diameter – 58mm, Maximum length – 117mm
- UNILUBE operating temperature range -20°C to +60°C
 - Dispensing periods indicated at +20°C unless otherwise specified
 - Higher temperatures can increase lubricant flow rate (reducing activator time setting)
 - Lower temperatures can reduce lubricant flow rate (increasing activator time setting)
- 5 bar maximum pressure at ROCOL UNILUBE outlet
- The ROCOL UNILUBE operates in any direction including fully submerged
- ATEX certified;

DEKRA 12 ATEX0006 X	IECEX DEK 11.0103X
II 1G Ex ia IIC T6	Ex ia IIC T6 Ga
II 1D Ex iaD 20 T85°C	Ex ia IIIC T85 °C Da
I M1 Ex ia I	Ex ia I Ma