

Performance you can trust

GLASSFLO 5000 Mould Pretreatment

GLASSFLO 5000 is a dry-film blank mould pre-treatment specially formulated to remove the need for manual swabbing of moulds during start-up, so giving consistent running conditions. GLASSFLO 5000 can also be applied to blow moulds, bottom plates, neck rings and other related equipment.

Features

- Clean, air cured, dry coating - requires no baking.
- Prevents adhesion of ware to moulds.
- Promotes excellent glass distribution.
- Cost efficient through reduced mould dope usage.
- Consistent quality through even film.

Directions for Use

1. Ensure surfaces are clean, dry and free from oil or grease.
2. Apply a thin, even coating in well ventilated conditions. GLASSFLO 5000 should be spray applied with suitable spray equipment.
3. For best results allow to cure at room temperature for 30 mins. GLASSFLO 5000 will be touch dry in 10 mins for handling purposes.
4. Clean spray equipment immediately after use to avoid blockage.
5. Lightly burnish the resulting film for an excellent finish to ware.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Performance you can trust

GLASSFLO 5000

Appearance	Thin, grey/black film
Solid Lubricant	Graphite
Binder	Organic resin
Solvent	Non-chlorinated
Storage	Storage at 0°C to 40°C. Do not allow to freeze.
Pack Sizes – Part codes	5 litre - 78867

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.