

## LAYOUT INK SPRAY BLUE

**Layout Ink Spray Blue is a specialised paint designed for the marking out of metal surfaces in Toolrooms, Machine shops etc. The thin, dry film enables clear, sharply defined lines to be scribed on most surfaces without flaking.**

**Layout Ink Spray Blue is designed for use on bright or machined surfaces.**

### Features

- Allows clear, sharp definitions.
- Will not chip or flake.
- Resists wash off, ie. Water mix cutting fluids.
- Easy to apply and remove.

### Directions for Use

1. Layout Ink Spray Blue should be applied to a grease/dirt free surface.
2. Shake well, hold upright and spray from a distance of 15-25cm (6-8ins).
3. Allow film to dry for a minimum of 2 minutes before use. Ensure adequate ventilation.

**N.B.** To avoid blockage, clear spray head after use by inverting can and depressing button for 2-3 seconds until jet is cleared.

Layout Ink Spray Blue can be easily removed with the use of a suitable solvent – ROCOL® Flawfinder Cleaner Spray.

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

# Technical Data

**ROCOL**<sup>®</sup>

Performance you can trust

## LAYOUT INK SPRAY BLUE

<b>Appearance</b>	Dark blue, dry film
<b>Propellant</b>	Butane/Propane
<b>Solvent</b>	Acetone and Isopropyl alcohol
<b>Flash Point</b>	<0°C
<b>Storage</b>	Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.
<b>Pack Sizes – Part Codes</b>	400ml - 57015

Date: Jul-09

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control or knowledge which affect the use and performance  
of our products, for which reason it is given without responsibility.