

MOULD RELEASE SPRAY Non-Silicone Dry Film Spray

Mould Release Spray is designed to give fast, efficient and clean release with faithful reproduction of the mould profile however complex the mould or minute the detail. Suitable for use on all plastic and rubber mould tools including injection, compression and blow mouldings.

Mould Release Spray penetrates and spreads to all parts of the most intricate moulds to give full, clean release whilst the dry film will not affect profiles or interfere with precision fits. Applied film has excellent adhesion, is non-staining, will not transfer to product and can be safely used without fear of blemish or any adverse effect on subsequent finishing operations.

Features

- Effective release of plastics and rubber moulded parts.
- Thin film - will not affect profiles or interfere with precision fits.
- Will not affect subsequent finishing operations
- Silicone free.

Directions for Use

Shake well, hold upright and spray from a distance of approximately 15-30cm (6-12 inches). One pass usually provides sufficient coating. Ensure adequate ventilation.

Do not spray onto naked flame or any incandescent material. When using do not smoke. Wash hands before smoking or handling tobacco products.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

MOULD RELEASE SPRAY

Propellant	Hydrocarbon blend
Solvent	Acetone
Base Solid	PTFE
Colour	Colourless
Temperature Range	Up to +270°C
Storage	Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight
Pack Sizes – Part Codes	400ml - 72021

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.