

Performance you can trust

PRETON R-303P Blank Wash and Forming Lubricant

PRETON R-303P is a high performance lubricant designed for cleaning, blanking and forming automotive components whilst also leaving a corrosion preventing residual film.

The product should be used undiluted in automotive blank washing systems incorporating sheet feeder/leveller equipment.

Features

- High performance giving minimal scrap.
- Strong cleaning action.
- Excellent penetrating properties.
- Excellent residual rust prevention.
- Suitable for most metals.

Directions for Use

PRETON R-303P may be applied by brush, drip or airless spray system (ROCOL Automatic Spray System) but is more commonly utilised in a re-circulating system incorporating particulate removal.

PRETON R-303P is supplied ready for use.

Appearance	Light brown liquid
Odour	
Density	0.84 (kg/litre)
Corrosion Resistance	
- Humidity Cabinet (JIS K-2246)	720 hours (no rust)
- Salt Spray (ATM B 117)	24 hours (no rust)
Flash Point	>70°C
Viscosity at 40°C	3.9 cSt
Storage	Normal storage requirements (0°C to 30°C). Do not allow to freeze
Pack Sizes – Part Codes	1000 litre - 85005

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.