

PRETON VISCOSITY MODIFIER

Preton Viscosity Modifier is a special additive designed to maintain systems running on Preton blank washing lubricants in optimum condition. The product reduces the in-sump viscosity without compromising lubricity additive levels, therefore maintaining forming performance.

The product should be used undiluted in automotive blank washing systems.

Features

- Reduces in-sump viscosity.
- Maintains lubricity additive level.
- Suitable for use with ROCOL® Preton blank washing products.

Directions for Use

Preton Viscosity Modifier is supplied ready for use.

| | |
|--------------------------------|--|
| Appearance | Light brown liquid |
| Odour | Characteristic |
| Density | 0.84 (kg/litre) |
| Flash Point | >70°C |
| Viscosity at 40°C | 3.4 cSt |
| Storage | Normal storage requirements (0°C to 30°C). Do not allow to freeze. |
| Pack Sizes – Part Codes | 1000 litre - 85035 |

Date: Aug-10

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.