

Performance you can trust



RAPIDSEAL



FOLIAC Rapid-Curing Pipe Sealant for Universal Applications

Product Overview

ROCOL® RAPIDSEAL is a fluorescent yellow compound for use as a thread sealant on industrial metal pipework (including stainless steel) up to 3" diameter.

ROCOL RAPIDSEAL has a rapid cure speed that minimises downtime in breakdown or repair situations.

Features and Benefits

- ROCOL RAPIDSEAL has an excellent temperature range from -50°C to +150°C.
- When fully cured ROCOL RAPIDSEAL can resist pressures up to 1000 bar (14,500 psi).
- ROCOL RAPIDSEAL is suitable for use with natural gas and LPG pipework - conforms to EN751-1.
- Suitable for use by registered gas installers.
- Thread locking action – eliminates vibration induced loosening.
- ROCOL RAPIDSEAL is NSF S2 listed and therefore acceptable for use in and around a food processing areas as a pipe sealant.
- WRAS (Water Regulations Advisory Scheme) approved material for use in contact with drinking water.
- ROCOL RAPIDSEAL replaces traditional paste/hemp combinations.
- Supplied in a convenient precision applicator which minimises waste, whilst its thixotropic nature reduces drips during application.

Specifications

- NSF S2 registered – 152681
- WRAS approved materials - 1910543

Directions for Storage and Use

- ROCOL RAPIDSEAL should not be applied in sub-zero temperatures.
- Ensure threads are completely clean and free of contaminants by using a suitable solvent cleaner such as ROCOL Industrial Cleaner Rapid Dry.
- Apply a single continuous bead of ROCOL RAPIDSEAL around the 2nd or 3rd male thread (for long thread engagements a second bead may be required further up the thread).
- Assemble the thread and tighten as per standard practice. Low pressure testing may be carried out immediately.
- Full cure time of ROCOL RAPIDSEAL will depend on ambient temperature etc. However, a full cure can take up to 6 hours.
- For natural gas and LPG installations the maximum thread size specified in EN751-1 is DN50 (2").
- The storage temperature should be controlled between +1°C and +40°C.
- Shelf life is 2 years from date of manufacture.

Typical Applications

- ROCOL RAPIDSEAL is ideal for sealing air, water (including potable), steam (up to 2 bar), natural gas, LPG, petrol, diesel, fuel oils, mineral oils, vegetable oils, alcohol and refrigerant gases.

Pack Sizes

For pack sizes and part codes please visit:
www.rocol.com or email:
customer.service@rocol.com

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTORS
IN PEOPLE

Performance you can trust



RAPIDSEAL

FOLIAC Rapid-Curing Pipe Sealant for Universal Applications

Property	Result
Appearance	Fluorescent yellow compound
Temperature Range	-50°C to +150°C
Pressure Resistance	1000 bar (14,500 psi)
Flash Point	>100°C
Brookfield Viscosity @ 25°C (2.5 rpm)	70,000cps
Curing Times:	
Low Pressure Seal	Immediate
Functional Strength	1-3 hours
Full Chemical Cure	3-6 hours
Maximum Thread Size	3" diameter (Natural gas & LPG up to 2")
Natural gas/LPG approval	Meets the requirements of EN751-1 class H. Suitable thread sizes DN10 to DN50 operating at pressures up to 5bar, temperature range -20°C to +125°C.

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 5 Date: 04-22

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer.service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds, LS26 8BS
Registered Company No 559693 VAT No 742 0531 67
Registered Office: Nexus House, Station Road, Egham, Surrey, TW20 9LB

ROCOL A division of **ITW** Ltd

