

Performance you can trust

RTD® Liquid Chlorine-Free Hand Applied Metal Cutting Lubricant

RTD® Liquid Chlorine-Free is a viscous fluid for use in reaming, tapping, and drilling and other metal cutting operations. RTD® Liquid Chlorine Free is suitable for all metals including hardened steels, nimonics and titanium alloys. RTD® Liquid Chlorine Free has been specifically developed to satisfy ever increasing environmental and health and safety needs in today's markets.

Features

- Extends tool life.
- Improves surface finish.
- Increases removal rates.
- Reduces production costs.

Directions for Use

RTD® Liquid Chlorine Free is applied straight to the cutting operation, it is also available in a handy squeeze bottle for ease of use. When used as a mineral cutting oil reinforcement, add between 1 and 5 parts of RTD® Liquid Chlorine Free to 100 parts of neat mineral cutting oil.

Appearance	Red liquid
Odour	Mild Sulphur
Solvents	None
Shell 4-Ball Weld Load	800kg
Tapping Torque (316 Stainless Steel)	8.6 NM
Corrosion (Steel Plate at 175°C for 5 minutes)	None
Storage	0° to 40°C. Normal storage
Pack Sizes – Part Codes	350ml - 53521
Pack Sizes – Part Codes	5L - 53526

Date: Nov-22

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.