

Performance you can trust

RTD[®] Foamcut Metal Cutting Lubricant Spray

RTD[®] Foamcut is a metal cutting lubricant specially formulated to provide extreme pressure cutting performance in an economical to use foaming aerosol. RTD[®] Foamcut is suitable for all metal cutting operations on a wide range of ferrous and non ferrous metals, including copper, brass and aluminium. The foaming action ensures the lubricant rapidly penetrates to the cutting edges without running off the tool or workpiece and allows economical application, even in deep holes. This prolongs tool life and improves surface finish.

Features

- Extends tool life.
- Improves surface finish.
- Increases removal rates.
- Reduces production costs.

Directions for Use

RTD[®] Foamcut should be shaken well before use then sprayed directly onto the tool or workpiece from a distance of 15 - 30 cm. The direction control straw allows greater accessibility to difficult operations and enables application exactly where needed.

Ensure adequate ventilation.

Appearance	Creamy-white foam
Odour	Mild
Solvents	None
Nitrites	None
Silicones	None
Storage	Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight
Pack Sizes – Part Codes	300ml - 53041

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.