

Performance you can trust

ULTRAGLIDE SPRAY Machine Tool Slideway Lubricant

ROCOL® Ultraglide Spray is specially designed to overcome “stickslip” phenomena and provide smooth and precise movement of machine tool slideways, collets and chucks. The extreme pressure agents and anti-wear additives reduce wear, while the adhesive qualities of the lubricant reduce draining to a minimum, ensuring effective performance over a long period of time.

Features

- Resists washing action of coolant and protects against corrosion.
- Provides lasting lubrication.
- Clings to vertical faces, and does not fling off rotating parts.
- Easy to apply into inaccessible areas.

Directions for Use

Shake well before use, hold upright and spray from a distance of 15 to 30cm.

Test compatibility with painted or coated surfaces, plastics and rubbers prior to application

Appearance (applied film)	Clear brown oil
Odour	Characteristic
Propellant	LPG
Solvent	Hydrocarbon
Kinematic Viscosity (applied film)	68 cSt at 40°C
Storage	Store below 50°C, keep out of direct sunlight
Pack Sizes – Part Codes	400ml - 52041

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.