

Performance you can trust

## ULTRACUT® 550 Extreme Pressure Neat Oil Cutting Fluid

**ULTRACUT® 550 is a pale coloured extreme pressure neat cutting oil formulated from severely refined mineral oil, lubricity additives and chlorinated EP performance additives. ULTRACUT® 550 provides excellent cutting performance and improves tool life.**

**ULTRACUT® 550 is suitable for a wide range of applications on automatic and multi-tool lathes even when machining high tensile steels. It is also suitable for specialised operations such as production thread grinding, broaching, hobbing and multi-cutter milling set-ups.**

### Features

- Pale coloured.
- Low odour.
- Excellent extreme pressure properties.
- Improves tool life.
- Good heat transfer properties.

### Directions for Use

ULTRACUT® 550 is supplied ready for use. Guard against water ingress.

ULTRACUT® 550 is suitable for machining both ferrous and non-ferrous materials.

<b>Appearance</b>	Pale yellow liquid
<b>Odour</b>	Mild
<b>Viscosity at 40°C</b>	25 cSt
<b>Density at 20°C</b>	0.92 g/cm <sup>3</sup>
<b>Storage</b>	Store at normal ambient temperature (5°C to 30°C)
<b>Pack Sizes – Part Codes</b>	200 ltr - 51619 1000 ltr - 51615

Date: Feb-09

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E customer-service@rocol.com  
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.